


1 x 7

CABLE GALVANISÉ À CHAUD


Diamètre po	Force de rupture minimum lb
1/64	40
1/32	185
3/64	375
1/16	500
5/64	800
3/32	1,200
1/8	2,100
1/4	6,650
3/8	15,400
7/16	20,800
1/2	26,900
9/16	35,000
5/8	42,400



7 x 7

CABLE GALVANISÉ À CHAUD


Diamètre po	Force de rupture minimum lb
3/64	270
1/16	480
5/64	650
3/32	920
1/8	1,700
5/32	2,600
3/16	3,700
1/4	6,100
5/16	9,200
3/8	13,300



7 x 19

CABLE GALVANISÉ À CHAUD


Diamètre po	Force de rupture minimum lb
1/16	480
3/32	1,000
1/8	2,000
5/32	2,800
3/16	4,200
7/32	5,600
1/4	7,000
5/16	9,800
3/8	14,400



7 x 7

CABLE ACIER INOXYDABLE 316


Diamètre po	Force de rupture minimum lb
1/4	7,650
3/8	16,200
1/2	30,200



1 x 19

CABLE ACIER INOXYDABLE 316


Diamètre po	Force de rupture minimum lb
1/16	467
1/8	1,780
5/32	2,800
3/16	4,000
1/4	6,900
5/16	10,600
3/8	14,800
1/2	27,000



7 x 19

CABLE ACIER INOXYDABLE 316


Diamètre po	Force de rupture minimum lb
3/32	700
1/8	1,300
5/32	2,000
3/16	2,900
1/4	4,900
5/16	7,600
3/8	11,000



19 x 7

CABLE ANTIGÉRATOIRE

Diamètre pouce	IPS
3/16	---
1/4	5,020
5/16	7,800
3/8	11,180
7/16	15,160
1/2	19,700
9/16	24,800
5/8	30,600
3/4	43,600
7/8	59,000
1	76,600



ÉTRANGLEUR 3 BOULES

Diamètre x long. po
7/16 x 5'
7/16 x 5' 6"
7/16 x 6'
7/16 x 6' 6"
7/16 x 7'
7/16 x 8'
1/2 x 6'
1/2 x 6' 6"
1/2 x 7'
1/2 x 8'
1/2 x 9'
1/2 x 10'
9/16 x 10'
9/16 x 11'
9/16 x 12'
9/16 x 13'
9/16 x 14'
9/16 x 15'

ÉTRANGLEUR À CHAÎNE

Diamètre x long. po
7/16 x 5'
7/16 x 5' 6"
7/16 x 6'
7/16 x 6' 6"
7/16 x 7'
7/16 x 8'
1/2 x 6'
1/2 x 6' 6"
1/2 x 7'
1/2 x 8'
1/2 x 9'
1/2 x 10'
9/16 x 10'
9/16 x 11'
9/16 x 12'
9/16 x 13'
9/16 x 14'
9/16 x 15'



RALLONGE D'ÉTRANGLEUR

- 7/16 X 18"
- 7/16 X 24"
- 1/2 X 18"
- 1/2 X 24"
- 9/16 X 18"
- 9/16 X 24"